






Plieno lynas 6X36 FC 1960N/mm²



Atsargos koef. 5:1 DS/EN 13414-1	1-os šakos			2-jų šakų		3-jų ir 4-ių šakų		Žiedas		
										
Apkrovos kampas	Tiesiai	Kilpa	U-forma	0° - 45°	45° - 60°	0° - 45°	45° - 60°	Tiesiai	Kilpa	U-forma
Apkrovos faktorius	1	0,8	2	1,4	1	2,1	1,5	2	1,6	4
mm	RDA, t									
8	0,75	0,6	1,5	1,1	0,75	1,6	1,1	1,4	1,2	3,0
9	0,9	0,8	1,8	1,26	0,9	2,0	1,4	1,8	1,5	3,6
10	1,2	0,95	2,4	1,7	1,2	2,5	1,8	2,4	1,9	4,8
11	1,4	1,1	2,8	2,0	1,4	3,0	2,2	2,8	2,3	5,6
12	1,7	1,3	3,4	2,4	1,7	3,6	2,6	3,4	2,7	6,8
13	2,0	1,6	4,0	2,8	2,0	4,2	3,0	4,0	3,2	8,0
14	2,3	1,8	4,6	3,2	2,3	4,8	3,5	4,6	3,7	9,2
16	3,0	2,4	6,0	4,2	3,0	6,3	4,5	6,0	4,8	12,0
18	3,8	3,1	7,6	5,3	3,8	8,0	5,7	7,6	6,1	15,2
20	4,7	3,8	9,4	6,6	4,7	10,0	7,1	9,4	7,6	18,8
22	5,7	4,6	11,4	8,0	5,7	12,0	8,5	11,4	9,2	23,0
24	6,8	5,4	13,6	9,5	6,8	14,3	10,2	13,6	11,0	27,0
26	8,0	6,4	16,0	11,2	8,0	16,8	12,0	16,0	12,8	32,0
28	9,3	7,4	18,6	13,0	9,3	19,5	14,0	18,6	15,0	37,0
32	12,0	9,7	24,0	16,8	12,0	25,5	18,0	24,0	19,5	48,0
36	15,0	12,0	30,0	21,0	15,0	32,0	23,0	30,0	25,0	60,0
40	19,0	15,0	38,0	27,0	19,0	40,0	28,5	38,0	30,0	76,0