

Plieno lynas 6X36 IWRC 1960N/mm²



Atsargos koef. 5:1 DS/EN 13414-1	1-os šakos			2-jų šakų		3-jų ir 4-ių šakų		Žiedas		
										
Apkrovos kampas	Tiesiai	Kilpa	U-forma	0° - 45°	45° - 60°	0° - 45°	45° - 60°	Tiesiai	Kilpa	U-forma
Apkrovos faktorius	1	0,8	2	1,4	1	2,1	1,5	2	1,6	4
mm	RDA, t									
8	0,8	0,65	1,6	1,15	0,8	1,7	1,2	1,6	1,3	3,2
9	1,05	0,8	2,1	1,45	1,05	2,2	1,8	2,1	1,7	4,2
10	1,3	1,0	2,6	1,8	1,3	2,7	1,9	2,6	2,0	5,2
11	1,5	1,2	3,0	2,2	1,5	3,3	2,3	3,0	2,5	6,0
12	1,8	1,4	3,6	2,6	1,8	3,9	2,8	3,6	3,0	7,2
13	2,2	1,8	4,4	3,0	2,2	4,5	3,2	4,4	3,5	8,8
14	2,5	2,0	5,0	3,5	2,5	5,3	3,8	5,0	4,0	10,0
16	3,3	2,6	6,6	4,6	3,3	6,9	4,9	6,6	5,2	13,2
18	4,1	3,3	8,2	5,8	4,1	8,7	6,2	8,2	6,6	16,4
20	5,1	4,1	10,2	7,2	5,1	10,7	7,7	10,2	8,2	20,4
22	6,2	5,0	12,4	8,7	6,2	13,0	9,3	12,4	10,0	24,8
24	7,4	5,9	14,8	10,3	7,4	15,5	11,1	14,8	11,8	29,6
26	8,7	7,0	17,4	12,1	8,7	18,2	13,0	17,4	13,8	34,8
28	10,0	8,0	20,0	14,0	10,0	21,0	15,0	20,0	16,0	40,0
32	13,0	10,4	26,0	18,4	13,0	27,5	19,7	26,0	21,0	52,0
36	16,6	13,3	33,0	23,0	16,6	35,0	25,0	33,0	26,5	66,0
40	20,5	16,4	41,0	29,0	20,5	43,0	31,0	41,0	33,0	82,0
44	25,0	20,0	50,0	35,0	25,0	52,0	37,0	50,0	40,0	100,0
48	29,5	23,6	59,0	41,0	29,5	62,0	44,0	59,0	47,0	118,0
52	35,0	28,0	70,0	48,0	35,0	73,0	52,0	70,0	55,0	140,0
56	40,0	32,0	80,0	56,0	40,0	84,0	60,0	80,0	64,0	160,0
60	46,0	37,0	92,0	65,0	46,0	97,0	69,0	92,0	74,0	184,0